

DECLARATION OF PERFORMANCE ADHESIVE PLASTER

Page: 1/1
Number: RF/04

1. Unique identification code of the product-type:	Building Plasters										
2. Type, batch or serial number or any other element allowing identification of the construction product trade name and contact address of the manufacturer in accordance with Article 11 (4):	RIGHTFINISH ADHESIVE PLASTER										
3. Intended use:	General Building Construction - It is used to bond of plasterboards to brickwork, blockwork, aerated concrete, concrete, etc. surfaces.										
4. Trade name and contact address of the manufacturer in accordance with Article 13 (5)	Dalsan Alçı Sanayi ve Ticaret A.Ş. - Kırşehir Bala Karayolu, 35. Km. Oğulbey Köyü Cıvarı, 06830 Gölbaşı, Ankara, TÜRKİYE										
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 14 (2):	N/A										
6. System or systems of assessment and verification of constancy of performance:	System 4										
7. Performance concerning a construction product covered by a harmonised standard:	<table><tr><td>EN 14496:2019</td><td>Gypsum based adhesives for thermal/acoustic insulation composite panels and gypsum boards</td></tr><tr><td>CE</td><td>Self Declaration</td></tr></table>	EN 14496:2019	Gypsum based adhesives for thermal/acoustic insulation composite panels and gypsum boards	CE	Self Declaration						
EN 14496:2019	Gypsum based adhesives for thermal/acoustic insulation composite panels and gypsum boards										
CE	Self Declaration										
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:	N/A										
9. Declared performance:	<table><thead><tr><th>Essential characteristics</th><th>Performance</th><th>Harmonised Technical Specification</th></tr></thead><tbody><tr><td>Reaction to Fire (Acc. to EN 13279 point 5.1.1)</td><td>A1</td><td rowspan="3">EN 14496:2019</td></tr><tr><td>Bond Strength</td><td>0,06 MPa</td></tr><tr><td>Dangerous Content</td><td>NPD</td></tr></tbody></table>	Essential characteristics	Performance	Harmonised Technical Specification	Reaction to Fire (Acc. to EN 13279 point 5.1.1)	A1	EN 14496:2019	Bond Strength	0,06 MPa	Dangerous Content	NPD
Essential characteristics	Performance	Harmonised Technical Specification									
Reaction to Fire (Acc. to EN 13279 point 5.1.1)	A1	EN 14496:2019									
Bond Strength	0,06 MPa										
Dangerous Content	NPD										
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.	This declaration of performance is issued, in accordance with Regulations (EU) No 305/2011, under the sole responsibility of the manufacturer specified in point 4.										

Signed for and on behalf of company by:
ANKARA / 20 March 2020



Şerafettin TURAN
Sales&Marketing Manager

RIGHTFINISH