

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

According to Regulation (EC) No : 1907/2006 Annex II as amended.  
Commission Regulation (EU) 2020/878 of June 2020"

#### 1.1. Product identifier

**Product name**  
RIGHTFINISH TOPCOAT

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

TOPCOAT is an under-paint, final coat finishing plaster having high adhering. TOPCOAT, can applicate to PRIMECOAT and COREX plasterboard surface.

Uses advised against No specific uses advised against are identified.

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Dalsan Alçı Sanayi ve Ticaret A.Ş.

##### Place of Production

Dalsan Alçı Sanayi ve Ticaret A.Ş.

Kaleboğazı Tesisleri

Ankara Bala Kırşehir Yolu, 35. Km.,

Oğulbey Köyü Civarı, 06830,

Gölbaşı, Ankara TURKEY

T: (90) 312 497 51 00

F: (90) 312 615 50 91

E-mail: kalebogazi@dalsan.com.tr

#### 1.4. Emergency telephone number

(90) 312 303 49 00

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008)

GHS05 corrosion

Eye dam 1H318 Cao-uses serious eye damage

##### Physical hazards

Not Classified

##### Health hazards

Not Classified

##### Environmental hazards

Not Classified

##### Human health

Plaster dust can be irritating to the skin, eyes, and respiratory tract. A small amount of cutting fluid can be found on profiles due to the nature of the production process. This liquid may cause skin irritation when repeated contact occurs.

#### 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008)

The Product is classified and labelled according to the CLP regulation.

##### Signal Word

Danger

##### Hazard - determining components of labelling

Calcium dihydroxide

##### Hazard statements

H318 Causes serious eye damage

#### 2.3. Other hazards

The mixture produces an alkaline reaction when the exposed to moisture. Please take this into consideration when processing the material and avoid extended contact with the skin or make sure to wear gloves

This product does not contain any substances classified as PBT or vPvB.

Avoid inhalation of dust. Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.

Result of PBT and vPvB assessment

PBT: Not applicable

vPvB: Not applicable

### SECTION 3: Composition/information on ingredients

Products may contain calcium sulfate, limestone, retarders, volumetric stabilizers.

#### Mixtures

##### Calcium sulfate hemihydrate

CAS Number: 7778-18-9 EC Number: 231 900-3

Reg Nr: 01-2119444918-26-XXXX

Substance with National workplace exposure limits

##### Calcium Dihydroxide

CAS Number: 7778-18-9 EC Number: 231 900-3

Eye Dam:1 H318; Skin Irrit 2 H315; STOT SE 3 H335

Substance with National workplace exposure limits

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.

##### Inhalation Move

affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.

##### Ingestion

Rinsemouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.

##### Skin contact

Brush off loose particles from skin. Remove affected person from source of contamination. Rinse immediately with plenty of water. Get medical attention if symptoms are severe or persist after washing.

##### Eye contact

Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes. Get medical attention if symptoms are severe or persist after washing.

##### Protection of first aiders

First aid personnel should wear appropriate protective equipment during any rescue.

#### 4.2. Most important symptoms and effects, both acute and delayed

##### General information

See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

##### Inhalation

Dust may irritate the respiratory system. Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.

##### Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting.

##### Skin contact

Prolonged contact may cause dryness of the skin. Plaster may form an alkaline solution on contact with body moisture or when mixed with water. May cause irritation. Redness.

Prolonged contact with moist or wet product may cause burns.

##### Eye contact

Particles in the eyes may cause irritation and smarting. Plaster may form an alkaline solution on contact with body moisture or when mixed with water. May cause irritation. Redness.

Prolonged contact with moist or wet product may cause burns.

#### 4.3. Indication of any immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically.

##### Specific treatments

No special treatment required.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

#### 5.2 Special hazards arising from the substance or mixture

##### Specific hazards

Plaster may form an alkaline solution when mixed with water. It is a Plaster Class A1 non-flammable material, but the packaging may burn. Standard methods and extinguishers are enough to put out the fire. For detailed information about firefighting classes, see EN 13279-1

#### 5.3 Required for firefighters

Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### Personal precautions

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with skin, eyes and clothing. Avoid inhalation of dust. Follow precautions for safe

handling described in this safety data sheet. Wash thoroughly after dealing with a spillage.

#### 6.2. Environmental precautions

##### Environmental precautions

Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

#### 6.3. Methods and material for containment and cleaning up

##### Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Reuse or recycle products wherever possible.

Approach the spillage from upwind. Avoid generation and spreading of dust. Small Spillages: Remove spillage with vacuum cleaner or collect with a shovel and broom, or similar. Large Spillages: Collect spillage with a shovel and broom, or similar and reuse, if possible. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage.

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Plaster dust and mortars should be prevented from mixing with waste water, streams, and the soil. For this purpose, accidentally spilled products should be collected.

#### 6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### Usage Precautions

Keep out of the reach of children. Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Keep container tightly sealed when not in use. Plaster may form an alkaline solution on contact with body moisture or when mixed with water. Avoid contact with eyes and prolonged skin contact. Avoid generation and spreading of dust. Avoid handling which leads to dust formation. Avoid inhalation of dust.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Storage precautions

Store away from incompatible materials (see Section 10). Store in a dry place. Store in accordance with local regulations.

##### Storage class

Unspecified storage.

#### 7.3. Specific end use(s)

Specific end use(s) Consider the following during handling:

- Firmly grab the load,
- Ensure that the hands, the load, and the handles are not slippery.
- The position of the feet and body should be over the load (or the body should be as close to the front of the load as possible),
- Use the leg muscles while lifting the load,
- Keep the back straight,
- Ensure that the arms are straight and facing down while lifting and carrying the load.

Wear protective clothing to avoid any possible discomfort resulting from skin contact of the products during handling.

Use forklifts in handling products delivered on palettes or in packages. Ensure that the handling capacity of the forklift is adequate and the forklift operator is licensed and experienced. Pile the products in a dry place in a way that they will not fall down (ensuring that there are a maximum of 20 bags in a pile).

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

#### Occupational exposure limits

<b>Calcium sulfate hemihydrate</b>
Long-term exposure limit (8-hour TWA): WEL 10 mg/m <sup>3</sup> inhalable dust Long-term exposure limit (8-hour TWA): WEL 4 mg/m <sup>3</sup> respirable dust
<b>Calcium dihydroxide</b>
Long-term exposure limit (8-hour TWA): WEL 5 mg/m <sup>3</sup> Long-term exposure limit (8-hour TWA): WEL 1 mg/m <sup>3</sup> Short-term exposure limit (15-minute): WEL 4 mg/m <sup>3</sup>
<b>Sodium hydroxide</b>
Short-term exposure limit (15-minute): WEL 2 mg/m <sup>3</sup> WEL = Workplace Exposure Limit.

### 8.2 Exposure controls

#### Inhaling

Ensure that the ventilation is adequate at the work site. Wear the appropriate FFP2S dust mask in line with TS EN 149 if ventilation is not possible.

#### Eyes

Wear Class 2A5 goggles in line with EN 166 to prevent possible contact.

#### Skin

Wear full work clothes with the right measurements to prevent repeating skin contact.

#### Hands

Wear protective gloves to minimize the effect of irritation. Apply protective hand creams.

## SECTION 9: Physical and chemical properties

<b>Appearance</b>	Powdery
<b>Odor</b>	Odorless
<b>pH</b>	neutral
<b>Color</b>	white
<b>Melting point</b>	No information available
<b>Initial boiling point and range</b>	Not applicable.
<b>Flash point</b>	Not applicable.
<b>Evaporation rate</b>	Not applicable.
<b>Evaporation factor</b>	Not applicable.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	Not applicable.
<b>Vapour pressure</b>	Not applicable.
<b>Relative density</b>	Not applicable.
<b>Solubility(ies)</b>	Not applicable.
<b>Partition coefficient</b>	Not applicable.
<b>Viscosity</b>	Not applicable.

## SECTION 10: Stability and reactivity

### 10.1. Reaktivite

See the other subsections of this section for further details.

### 10.2. Chemical stability

Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

### 10.3. Possibility of hazardous reactions

No potentially hazardous reactions known.

### 10.4. Conditions to avoid

Avoid handling which leads to dust formation.

### 10.5. Incompatible materials

Avoid contact with acids.

### 10.6. Hazardous decomposition products

Hazardous decomposition products

## SECTION 11: Toxicological information

<b>Inhaling</b>	Ensure that the ventilation is adequate at the work site. Wear the appropriate FFP2S dust mask in line with EN 149 if ventilation is not possible.
<b>Eyes</b>	Wear Class 2A5 goggles in line with EN 166 to prevent possible contact
<b>Skin</b>	Wear full work clothes with the right measurements to prevent repeating skin contact.
<b>Hands</b>	Wear protective gloves to minimize the effect of irritation. Apply protective hand creams.

## SECTION 12: Ecological information

### 12.1. Toxicity

Not regarded as dangerous for the environment

### 12.2. Persistence and degradability

Stable products do not have any known side effects.

### 12.3. Bioaccumulative potential

No data available on bioaccumulation

### 12.4. Mobility in soil

Hardens in contact with water.

### 12.5. Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB

### 12.6. Other adverse effects

None known.

## SECTION 13: Disposal considerations

The disposal of waste is the responsibility of the user. The user should follow and abide by the current legislation

**SECTION 14: Transport information**

**14.1. UN number**

Not applicable.

**14.2. UN proper shipping name**

Not applicable.

**14.3. Transport hazard class(es)**

No transport warning sign required.

**14.4. Packing group**

Not applicable.

**14.5. Environmental hazards**

Environmentally hazardous substance/marine pollutant No.

**14.6. Special precautions for user Not applicable.**

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Not applicable

**SECTION 15: Regulatory information**

For occupational exposure limits, see <http://www.ilo.org/public/english/protection/safework/cis/products/icsc/dtasht/index.htm>

For product standards, see EN 13279-1

**SECTION 16: Other information**

This Material Safety Data Sheet had been prepared with the current knowledge and experience of Dalsan. This document contains the health and safety considerations during handling, storage, and use of building materials of Dalsan and the precautions that can be taken against such risks; it does not substitute for product specifications and warranties. This document contains the minimum information for health and safety. It does not contain all the health and safety precautions that need to be taken since it is not possible to forecast all the occupational safety risks that the user can face during operation. In short, this does not replace the risk assessment that needs to be performed at the work site by the user and/or cannot be used alone for the risk assessment. The building materials mentioned in this document are designed to be used within the framework of the purposes described in technical documents of Dalsan. Refer to our Technical Service or [www.dalsan.com.tr](http://www.dalsan.com.tr) for more information or up-to-date technical documents about our products. Following the changes and updated documents is the responsibility of the users

**Reach number : 01-2119444918-26-XXXX**

**H315 Causes skin Irriation**

**H318 Causes serious eye damage**

**H335 May cause respiratory irritation.**

**DOCUMENT CODE : GF-XSDS-06**

**REVISION DATE : 07.03.2023**

**REVISION NUMBER :0**