

# DECLARATION OF PERFORMANCE TOPCOAT

Page: 1/1  
Number: RF/07

1. Unique identification code of the product-type:	Building Plasters										
2. Type, batch or serial number or any other element allowing identification of the construction product trade name and contact address of the manufacturer in accordance with Article 11 (4):	RIGHTFINISH TOPCOAT C6 -Thin Coat Plaster, Finishing Product										
3. Intended use:	TOPCOAT is an under-paint, final coat finishing plaster having high adhering. TOPCOAT, can applicate to PRIMECOAT and COREX plasterboard surface.										
4. Trade name and contact address of the manufacturer in accordance with Article 13 (5)	Dalsan Alçı Sanayi ve Ticaret A.Ş. - Kırşehir Bala Karayolu, 35. Km. Oğulbey Köyü Cıvarı, 06830 Gölbaşı, Ankara, TÜRKİYE										
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 14 (2):	N/A										
6. System or systems of assessment and verification of constancy of performance:	System 4										
7. Performance concerning a construction product covered by a harmonised standard:	<table><tr><td>EN 13279-1:2009</td><td>Gypsum binders and gypsum plasters - Part 1: Definitions and requirements</td></tr><tr><td>CE</td><td>Self Declaration</td></tr></table>	EN 13279-1:2009	Gypsum binders and gypsum plasters - Part 1: Definitions and requirements	CE	Self Declaration						
EN 13279-1:2009	Gypsum binders and gypsum plasters - Part 1: Definitions and requirements										
CE	Self Declaration										
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:	N/A										
9. Declared performance:											
	<table><thead><tr><th>Essential characteristics</th><th>Performance</th><th>Harmonised Technical Specification</th></tr></thead><tbody><tr><td>Reaction to Fire (Acc. to EN 13279-1:2009 point 5.1.1)</td><td>A1</td><td rowspan="3">EN 13279-1:2009</td></tr><tr><td>Airborne Sound Insulation</td><td>NPD</td></tr><tr><td>Thermal Conductivity</td><td>0,34 W/(m.K)</td></tr></tbody></table>	Essential characteristics	Performance	Harmonised Technical Specification	Reaction to Fire (Acc. to EN 13279-1:2009 point 5.1.1)	A1	EN 13279-1:2009	Airborne Sound Insulation	NPD	Thermal Conductivity	0,34 W/(m.K)
Essential characteristics	Performance	Harmonised Technical Specification									
Reaction to Fire (Acc. to EN 13279-1:2009 point 5.1.1)	A1	EN 13279-1:2009									
Airborne Sound Insulation	NPD										
Thermal Conductivity	0,34 W/(m.K)										
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.	This declaration of performance is issued, in accordance with Regulations (EU) No 305/2011, under the sole responsibility of the manufacturer specified in point 4.										

Signed for and on behalf of company by:  
ANKARA / 20 March 2023

Şerafettin TURAN  
Sales&Marketing Manager